

LS32 2150A AC LS322150A1FPB000 32-Way Active Splitter (950-2150 MHz)



General Description:

The **LS322150A1FPB000** is a commercial quality 32-way splitter that meets strict level and match specifications achieved through the use of Quintech's proprietary microstrip and SMT technology. It operates over the 950-2150 MHz frequency range and permits signal splitting with zero loss, eliminating the need for external distribution amplifiers. The LS322150A1FPB000 provides LNB DC power insertion that can be switched on or off via the front panel mounted slide switch (see LNB Power specification below).

Note: All unused RF output ports must have 75 Ω terminations.

Specifications:

Frequency:	950-2150 MHz
Impedance:	75 Ω
P1dB:	-10 dBm
Insertion Loss:	0 <u>+</u> 2 dB
Frequency Response:	<u>+</u> 2 dB
Isolation:	18 dB
Input Return Loss:	12 dB
Output Return Loss:	12 dB
Noise Figure:	12 dB
RF Connectors:	Type F, 75 Ω
Power Requirements:	100-240 V~, 60/50 Hz
LNB Power:	24 V (700 mA max. available for LNB power)
Power Consumption:	5 W (plus customer LNB power load)
Mechanical:	2 RU (3.5" H x 19" W x 14" D)
Weight:	10.4 lbs. gross (boxed), 6.4 lbs. net
Certifications:	CE



250 Airport Road • Indiana, PA 15701 • (800) 839-3658 • (724) 349-1412 • Fax: (724) 349-1421 http://www.quintechelectronics.com/ • info@quintechelectronics.com

© 2009 Quintech Electronics and Communications Inc. All rights reserved. All product designs and specifications are subject to change without notice. LS322150A1FPB000 Rev C, CO# 13678 (Page 1 of 1)